602,951-



Docket No.: TESSERA 3.0-113/CONT

(PATENT)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Letters Patent of:

Belgacem Haba

Patent No.: 6,820,330 B

Issued: November 23, 2004

For: METHOD FOR FORMING A MULTI-LAYER

CIRCUIT ASSEMBLY

Certificate FEB 0 8 2005

of Correction

Certificate of Correction Branch Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

REQUEST FOR CERTIFICATE OF CORRECTION PURSUANT TO 37 CFR 1.323

Dear Sir:

Enclosed herewith is an original and one copy of a Certificate of Correction with respect to the above-identified U.S. Patent. You are hereby authorized to charge Deposit Account No. 12-1095 in the amount of \$100 to cover the required fee for filing a Certificate of Correction under § 1.323.

These errors were inadvertent, occurred in good faith and do not involve any changes which constitute new matter.

02/07/2005 BABRAHA2 00000006 121095 6820330 100.00 DA 01 FC:1811

Application No.: 09/602,951 Docket 1

Docket No.: TESSERA 3.0-113 CONT

We look forward to early return of the copy of the Certificate of Correction duly certified.

Dated: January 31, 2005

Respectfully submitted,

Daryl K. Neff

Registration No.: 38,253
LERNER, DAVID, LITTENBERG,
KRUMHOLZ & MENTLIK, LLP
600 South Avenue West
Westfield, New Jersey 07090

(908) 654-5000

Attorney for Applicant

541332_1.DOC

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO.

6,820,330 B)

DATED

November 23, 2004

INVENTOR(S)

Belgacem Haba

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 1, line 62, after "about", delete --are--.

Column 1, line 62, after "18' insert --microns--.

Column 2, line 9, "well know" should read --well-known--.

Column 2, line 9, "during" should read --drilling--.

Column 3, line 9, "nickellchrome" should read --nickel/chrome--.

Column 3, line 15, after "overlying" delete --,--.

Column 4, line 15, after "reference" insert --.--.

Column 4, lines 46-52 should read --In other embodiments, additional signal lines may be formed in at least one of the first and second metal layers before the coating step. For example, signal paths for carrying critical signals may be etched into the first and second metal layers, and the signal paths insulated during the coating with a dielectric material step .--

Column 5, line 39, "and-the" should read -- and the --.

Column 8, line 31, after "Patent" insert -- No. 5,282,312, the disclosure of which is incorporated herein by reference."

MAILING ADDRESS OF SENDER: Daryl K. Neff LERNER, DAVID, LITTENBERG, KRUMHOLZ & MENTLIK, LLP 600 South Avenue West Westfield, New Jersey 07090

PATENT NO. 6,820,330

No. of additional copies 1